

NIOC – RIPI
TBP DISTILLATION ANALYSIS
EXPORT BAHREGAN CRUDE OIL

SP.GR @15.56/15.56 °C: 0.8871

FRAC. NO	BOILING RANGE OF FRAC.@760 mmHg°C	WEIGHT PERCENT	CUTTING RANGE WT%	SP.GR @15.56 /15.56 °C	VOLUME PERCENT	CUTTING RANGE VOL %
1	IBP-15	0.96	0.96	0.5581	1.53	1.53
2	15-65	2.20	3.16	0.6447	3.03	4.56
3	65-100	4.11	7.27	0.7161	5.09	9.65
4	100-125	2.95	10.22	0.7426	3.52	13.17
5	125-150	3.59	13.81	0.7648	4.16	17.33
6	150-175	3.73	17.54	0.7819	4.23	21.56
7	175-200	3.47	21.01	0.7966	3.86	25.42
8	200-225	3.33	24.34	0.8158	3.62	29.04
9	225-250	3.51	27.85	0.8266	3.77	32.81
10	250-275	4.81	32.66	0.8419	5.07	37.88
11	275-300	3.94	36.60	0.8568	4.08	41.96
12	300-325	2.38	38.98	0.8607	2.45	44.41
13	325-350	5.25	44.23	0.8736	5.33	49.74
14	350-385	5.48	49.71	0.8876	5.48	55.22
15	385-425	4.07	53.78	0.9257	3.90	59.12
16	425-450	4.54	58.32	0.9321	4.32	63.44
17	450-475	5.26	63.58	0.9452	4.93	68.37
18	475-500	4.81	68.39	0.9540	4.47	72.84
19	500-530	3.65	72.04	0.9652	3.35	76.19
20	530-565	4.90	76.94	0.9788	4.44	80.63
21	565+	23.06	100.00	1.0560	19.37	100.00