

## EXPORT DORUD CRUDE OIL

TABLE : 1

<i>GENERAL DATA</i>				
<i>SPECIFICATION</i>		<i>RESULT</i>	<i>TEST METHOO</i>	
SPECIFIC GRAVITY @15.56/15.56 °C		0.8610	ASTM	D-4052
API		32.84	"	D-4052
SULPHUR CONTENT	WT%	2.9	"	D-2622
H2C CONTENT	PPM	52	RIPI	
NITROGEN TOTAL	WT%	0.10	"	D-3228
BASE SEDUNEBT & WATER	VOL%	TRACE<0.05	"	D-96
WATER CONTENT	VOL%	TRACE<0.05	"	D-95
SALT CONTENT	P.T.B	6	"	D-3230
KINEMATIC VISCOSITY @10 °C	c. St.	16.5	"	D-445
"	" @20 °C	10.8	"	D-445
"	" @40 °C	5.7	"	D-445
POUR POINT	°C	-11	"	D-97
R.V.P.	PSI	4.0	"	D-323
ASPHALTENES	WT%	3.1	IP-143	
WAX- CONTENT	WT%	5.5	BP-237	
DROP MELTING POINT OF WAX	°C	6	IP-31	
CARBON RESIDUE (CONRD. )	WT%	5.8	ASTM	D-189
ACIDITY TOTAL	MgKOH/gr	0.50	"	D-664
NICKEL	PPM	8.1	UOP-800	
VANADIUM	PPM	32.0	UOP-800	
IRON	PPM	1.0	UOP-800	
LEAD	PPM	<1.0	UOP-391	
SODIUM	PPM	38.0	UOP-391	

WORKED BY : CRUDE EVALUATION GROUP  
 APPROVED BY : H. TALACHI

DATE : November 2004