

**NIOC – RIPI**  
**TBP DISTILLATION ANALYSIS**  
**FORUZAN EXPORT CRUDE OIL**

**SP.GR @15.56/15.56 ° C: 0.8653**

<b>FRAC. NO</b>	<b>BOILING RANGE OF FRAC.@760 mmHg °C</b>	<b>WEIGHT PERCENT</b>	<b>CUTTING RANGE WT%</b>	<b>SP.GR @15.56 /15.56 ° C</b>	<b>VOLUME PERCENT</b>	<b>CUTTING RANGE VOL %</b>
1	IBP-15	1.00	1.00	0.5701	1.52	1.52
2	15-65	2.46	3.46	0.6361	3.35	4.87
3	65-100	5.59	9.05	0.6933	6.98	11.85
4	100-125	2.96	12.01	0.7336	3.49	15.34
5	125-150	5.05	17.06	0.7545	5.79	21.13
6	150-175	4.66	21.72	0.7717	5.23	26.36
7	175-200	4.20	25.92	0.7862	4.62	30.98
8	200-225	3.35	29.27	0.8010	3.62	34.60
9	225-250	4.10	33.37	0.8123	4.37	38.97
10	250-275	4.22	37.59	0.8311	4.39	43.38
11	275-300	4.49	42.08	0.8441	4.60	47.96
12	300-325	3.06	45.14	0.8572	3.09	51.05
13	325-350	3.17	48.31	0.8679	3.16	54.21
14	350-385	6.78	55.09	0.8889	6.60	60.81
15	385-425	6.16	61.25	0.9201	5.79	66.60
16	425-450	3.92	65.17	0.9324	3.64	70.24
17	450-475	4.49	69.66	0.9485	4.10	74.34
18	475-500	3.32	72.98	0.9561	3.00	77.34
19	500-530	3.40	76.38	0.9664	3.04	80.38
20	530-565	3.55	79.93	0.9803	3.13	83.51
21	565+	20.07	100.00	1.0532	16.49	100.00