

NIOC – RIPI
TBP DISTILLATION ANALYSIS
EXPORT HEAVY CRUDE OIL

SP.GR @15.56/15.56 °C: 0.8763

FRAC. NO	BOILING RANGE OF FRAC.@760 mmHg °C	WEIGHT PERCENT	CUTTING RANGE WT%	SP.GR @15.56 /15.56 °C	VOLUME PERCENT	CUTTING RANGE VOL %
1	IBP-15	2.15	2.15	0.5375	3.51	3.51
2	15-65	2.99	5.14	0.6442	4.07	7.58
3	65-100	4.39	9.53	0.7106	5.41	12.99
4	100-125	3.16	12.69	0.7442	3.72	16.71
5	125-150	3.59	16.28	0.7643	4.12	20.83
6	150-175	3.96	20.24	0.7797	4.45	25.28
7	175-200	3.25	23.49	0.7926	3.59	28.87
8	200-225	3.91	27.40	0.8123	4.22	33.09
9	225-250	3.23	30.63	0.8241	3.43	36.52
10	250-275	4.08	34.71	0.8394	4.26	40.78
11	275-300	3.93	38.64	0.8561	4.02	44.80
12	300-325	4.12	42.76	0.8575	4.21	49.01
13	325-350	4.23	46.99	0.8795	4.21	53.22
14	350-385	5.58	52.57	0.8919	5.48	58.70
15	385-425	2.65	55.22	0.9236	2.52	61.22
16	425-450	5.75	60.97	0.9316	5.41	6.63
17	450-475	5.30	66.27	0.9473	4.91	71.54
18	475-500	3.53	69.80	0.9556	3.24	74.78
19	500-530	3.68	73.48	0.9640	3.34	78.12
20	530-565	4.55	78.03	0.9780	4.08	82.20
21	565+	21.97	100.00	1.0815	17.80	100.00