

NIOC – RIPI
TBP DISTILLATION ANALYSIS
LAVAN EXPORT CRUDE OIL

SP.GR @15.56/15.56 °C: 0.8459

FRAC. NO	BOILING PANGE OF FRAC.@ 760 mmHg °C	WEIGHT PERCENT	CUTTING RANGE WT%	SP.GR @15.56/15.56 °C	VOLUME PERCENT	CUTTING RANGE VOL %
1	IBP-15	2.10	2.10	0.5589	3.18	3.18
2	15-65	4.09	6.19	0.6319	5.48	8.66
3	65-100	5.32	11.51	0.6997	6.43	15.09
4	100-125	4.15	15.66	0.7367	4.77	19.86
5	125-150	4.61	20.27	0.7624	5.11	24.95
6	150-175	4.73	25.00	0.7796	5.13	30.10
7	175-200	4.55	29.55	0.7907	4.87	34.97
8	200-225	3.62	33.17	0.8063	3.80	38.77
9	225-250	4.34	37.51	0.8176	4.49	43.26
10	250-275	4.76	42.27	0.8345	4.83	48.09
11	275-300	4.61	46.88	0.8474	4.60	52.69
12	300-325	4.48	51.36	0.8594	4.41	57.10
13	325-350	4.12	55.48	0.8782	3.97	61.07
14	350-385	6.74	56.22	0.8891	6.41	67.48
15	385-425	4.88	67.10	0.9200	4.48	71.96
16	425-450	4.93	72.03	0.9293	4.49	76.45
17	450-475	3.87	75.90	0.9454	3.46	79.91
18	475-500	3.14	79.04	0.9527	2.79	82.70
19	500-530	3.13	82.17	0.9615	2.75	85.45
20	530-565	3.48	85.65	0.9745	3.02	88.47
21	565+	14.35	100.00	1.0530	11.53	100.00