

TBP DISTILLATION ANALYSIS

SIRI EXPORT CRUDE OIL

SP.GR @15.56/15.56 °C: 0.8586

FRAC. NO	BOILING RANGE OF FRAC.@760 mmHg °C	WEIGHT PERCENT	CUTTING RANGE WT%	SP.GR @15.56 /15.56 °C	VOLUME PERCENT	CUTTING RANGE VOL %
1	IBP-15	1.83	1.83	0.5483	2.87	2.87
2	15-65	3.90	5.73	0.6488	5.16	8.03
3	65-100	4.95	10.68	0.7146	5.95	13.98
4	100-125	3.27	13.95	0.7429	3.78	17.76
5	125-150	4.94	18.89	0.7598	5.58	23.34
6	150-175	3.97	22.86	0.7797	4.37	27.71
7	175-200	4.33	27.19	0.7919	4.69	32.40
8	200-225	3.91	31.10	0.8149	4.12	36.52
9	225-250	4.50	35.60	0.8271	4.67	41.19
10	250-275	4.17	39.77	0.8451	4.24	45.43
11	275-300	4.99	44.76	0.8577	5.00	50.43
12	300-325	4.26	49.02	0.8691	4.21	54.64
13	325-350	4.37	53.39	0.8876	4.23	58.87
14	350-385	5.60	58.99	0.8956	5.37	64.24
15	385-425	5.38	64.37	0.9254	4.99	69.23
16	425-450	5.51	69.88	0.9387	5.04	74.27
17	450-475	4.13	47.01	0.9547	3.71	77.98
18	475-500	3.37	77.38	0.9621	3.01	80.99
19	500-530	3.33	80.71	0.9692	2.95	83.94
20	530-565	3.87	84.58	0.9806	3.39	87.33
21	565+	15.42	100.00	1.0445	12.67	100.00